

ET1294B

BMW BALL JOINT PULLER (24 mm & 27mm & 31 mm & 36mm)



VIDEO



Parts No.	Description
A1294-1	compression bar 159L
A1294-2	Base tool (27mm)
A1294-3	screw rod (M16×P1.5×11L)
A1294-4	Hexagon Screws(H24,M20×P1.5×98L)
A1294-5	bearing (φ10×43L)
A1294-6	Base tool (31mm)
A1294-7	Base tool (24mm)
A1294-8	Screw for Mini cooper
A1294-9	Base tool (36mm)





BENZ W220



PORSCHE 996 Carrera



AUDI A4



AUDI A6

- For quick and easy separation of ball joint connectors.
- A1294-6 is particularly useful for control arms from steering knuckle. Special for E53, E83.
- Application: BMW E38, E39, E52, E53, E60, E61, E70, E83, E90, E91, E92, R50, R52, R53, RR1, RR2, X5,
- A1294-7 Can be used for Mercedes E-Class (W211), CLS (W219), S-Class (W220) and SL(W230) · PORSCHE 996 · AUDI A4 · AUDI A6 Carrera lower suspension ball joint
- A1294-9 Can be used on BMW (E70) · Land Rover
- A1294-2 and 6 Can be used on Land Rover 4000c.c.(V8)

